



Product

Type

Hot Rod HR 15W-50

**High Performance
Synthetic Engine Oil**

Hot Rod HR 15W-50 Synthetic Engine Oil Product Information:

- Unique, full synthetic high performance motor oil.
- Designed for Hot Rod, Vintage, and Classic cars.
- Provides engine protection on the street, on the track, and in your garage.
- Contains the same additive technology used by the US Military for storing and shipping combat equipment worldwide.
- Protects against rust and corrosion during storage and operation.
- Higher levels of zinc antiwear compared to conventional passenger car motor oil to protect older style push-rod and flat tappet engines.
- Synthetic base stocks provide improved cold-start protection compared to conventional motor oils.
- Viscosity typical of SAE 15W-50.

Typical Physical Characteristics

PARAMETER	TEST METHOD	VALUE
Pounds per U.S. gallon at 15.6°C	----	7.15
Specific Gravity at 15.6°C	ASTM D1298	0.858
Viscosity at 40°C, cSt	ASTM D445	140
Viscosity at 100°C, cSt	ASTM D445	19.8
Viscosity Index	ASTM D2270	163
Cranking Viscosity at -20°C	ASTM D5293	5000
Zinc, wt%	ASTM D4951	0.127
Flash Point (PMCC), °C	ASTM D93	197
Pour Point, °C	ASTM D97	-42